

# Arcadia Pantile



## Fittings and accessories

Tile fittings: - LH verge tile  
- Dentil slips

Ridges: - Clay half round  
- Hogsback

Mono ridges: - Clay half round

Hips: - Clay third round  
- Hogsback

Valleys: - Lead  
- Fibreglass

Clips: - Tile

See pages 22-25.

## Roofing systems

Ventilation systems: - Ridge  
- Eaves  
- Top abutment  
- Tile  
- Gas terminals

See pages 64-77.

**The Arcadia Pantile provides the look of an aged pantile from the day it is placed on the roof. It replicates the charm and character of reclaimed pantiles, backed with Sandtoft's 60 year guarantee.**

## Technical data

Minimum roof pitch	30°
Headlap (minimum)	72 mm
Batten spacing at max. gauge	270 mm
Size of tile	342 x 252 mm
Covering capacity at max. gauge (tiles per m <sup>2</sup> )	17.5
Cover width	210 mm
Profile depth	69 mm
Hanging length	308 mm
Weight as laid (kg per m <sup>2</sup> )	41.1
Weight per 1000	2.4 tonnes
Weight per tile	2.4 kg
Weight per pallet (including pallet/packaging)	1.2 tonnes
Quantity per pallet	480
Battens per m <sup>2</sup>	3.7 m
Batten size	
Up to 450 mm rafter centres	38 x 25 mm
Up to 600 mm rafter centres	50 x 25 mm
Nail size/type for tiles	50 x 3.35 mm aluminium clout head

Note: Unless otherwise stated, data is based on tiles laid at minimum headlap.

## Colour



70 Reclaimed



Award winner