

Bridgwater Double Roman



Fittings and accessories

Ridges:	- Clay half round - Hogsback
Mono ridges:	- Clay half round
Hips:	- Clay third round - Hogsback
Valleys:	- Lead - Fibreglass
Clips:	- Tile, Eaves, Verge

See pages 44-49.

Roofing systems

Ventilation systems:	- Ridge - Eaves - Top abutment - Tile vent - Gas terminals
----------------------	--

See pages 64-77.

The Sandtoft Bridgwater has been designed to satisfy the need for an authentic traditional clay double roman tile traditionally manufactured in the South West of England.

Technical data

Minimum roof pitch	30°
Headlap (minimum)	75 mm
Batten spacing at max. gauge	345 mm
Size of tile	420 x 340 mm
Covering capacity at max. gauge	9.5 tiles per m ²
Cover width	305 mm
Profile depth	42 mm
Hanging length	403 mm
Weight as laid	43.7 kg per m ²
Weight per 1000	4.6 tonnes
Weight per tile	4.6 kg
Weight per pallet (including pallet/packaging)	0.9 tonnes
Quantity per pallet	186
Battens per m ²	2.9 m
Batten size	
Up to 450 mm rafter centres	38 x 25 mm
Up to 600 mm rafter centres	50 x 25 mm
Nail size/type for tiles	38 x 3.35 mm aluminium clout head
Nail size/type for tile clips	65 x 3.35 mm aluminium clout head

Note: Unless otherwise stated, data is based on tiles laid at minimum headlap.

Colour



Due to the traditional design of this product and the manufacturing process used, there may be some slight dimensional variations.