

# County Pantile



## Fittings and accessories

Tile fittings:	- LH verge tile - Dentil slips
Ridges:	- Clay half round
Mono ridges:	- Clay half round
Hips:	- Clay third round
Valleys:	- Lead - Fibreglass
Eaves:	- Bird comb filler
Clips:	- Tile, Eaves, Verge

See pages 22-25.

## Roofing systems

Dry roof systems:	- Ridge - Verge
Ventilation systems:	- Ridge - Eaves - Top abutment - Tile - Gas terminals

See pages 64-77.


**Combines the visual qualities of a traditional clay pantile, with the enhanced performance of a double interlocking design.**

## Technical data


Minimum roof pitch	22.5°
Headlap (average)	64 mm
Batten spacing at ave. gauge	320 mm
Size of tile	384 x 267 mm
Covering capacity at max. gauge (tiles per m <sup>2</sup> )	14.9
Cover width	210 mm
Profile depth	67 mm
Hanging length	352 mm
Weight as laid (kg per m <sup>2</sup> )	41
Weight per 1000	2.8 tonnes
Weight per tile	2.8 kg
Weight per pallet (including pallet/packaging)	1.3 tonnes
Quantity per pallet	456
Battens per m <sup>2</sup>	14.9 m
Batten size	
Up to 450 mm rafter centres	38 x 25 mm
Up to 600 mm rafter centres	50 x 25 mm
Nail size/type for tiles	38 x 3.35 mm aluminium clout head

Note: Unless otherwise stated, data is based on tiles laid at minimum headlap.


## Colours




65 Natural Red



66 Flanders



68 Antique Slate



69 Tuscan