

Gaelic



A specialist clay tile with a delicate single roll, Gaelic is ideal for refurbishment or new build work in conservation areas.

Technical data

Minimum roof pitch	30°
Headlap (minimum)	75 mm
Batten spacing at max. gauge	267 mm
Size of tile	342 x 255 mm
Covering capacity at max. gauge	16.8 tiles per m ²
Cover width	220 mm
Profile depth	43 mm
Hanging length	315 mm
Weight as laid	40.3 kg per m ²
Weight per 1000	2.4 tonnes
Weight per tile	2.4 kg
Weight per pallet (including pallet/packaging)	0.7 tonnes
Quantity per pallet	260
Battens per m ²	3.7 m
Batten size	
Up to 450 mm rafter centres	38 x 25 mm
Up to 600 mm rafter centres	50 x 25 mm
Nail size/type for tiles	50 x 3.35 mm aluminium clout head

Note: Unless otherwise stated, data is based on tiles laid at minimum headlap.

Fittings and accessories

Tile fittings:	- LH verge tile
Ridges:	- Clay half round - Hogsback
Mono ridges:	- Clay half round
Hips:	- Clay third round - Hogsback
Valleys:	- Lead - Fibreglass

See pages 44-49.

Roofing systems

Ventilation systems:	- Ridge - Eaves - Top abutment - Tile vent - Gas terminals
----------------------	--

See pages 64-77.

Colour

