

Humber Plain Tile



Humber Flanders


A traditional, cross-cambered, machine made clay plain tile. Gives complete design flexibility and is perfect for complex roofs or vertical cladding.

Technical data	Roof	Vertical
Minimum roof pitch	35°	75°
Headlap (minimum)	65 mm	38 mm
Batten spacing at max. gauge	100 mm	114 mm
Size of tile	265 x 165 mm	265 x 165 mm
Covering capacity at max. gauge	60.0 tiles per m ²	53.0 tiles per m ²
Cover width	165 mm	165 mm
Profile depth	13 mm	13 mm
Hanging length	245 mm	245 mm
Weight as laid	68.4 kg per m ²	60.4 kg per m ²
Weight per 1000	1.1 tonnes	1.1 tonnes
Weight per tile	1.1 kg	1.1 kg
Weight per pallet (including pallet/packaging)	0.6 tonnes	0.6 tonnes
Quantity per pallet	500	500
Battens per m ²	10 m	8.7 m
Batten size		
Up to 450 mm rafter centres	38 x 25 mm	38 x 25 mm
Up to 600 mm rafter centres	38 x 25 mm	38 x 25 mm
Nail size/type for tiles	38 x 3.35 mm aluminium clout head	

Note: Unless otherwise stated, data is based on tiles laid at minimum headlap.

Feature tile

Club pattern available.



Fittings and accessories

Tile fittings:	- Tile-and-a-half tiles - Eaves/tops tiles - Cloaked verge tiles (LH & RH) - External & internal angles (LH & RH)
Feature tiles:	- Club
Ridges:	- Clay half round
Mono ridges:	- Clay half round
Hips:	- Bonnet - Arris - Clay third round
Valleys:	- Valley tiles - Lead - Fibreglass

See pages 44-49.

Roofing systems

Dry roof system:	- Ridge - Hip
Ventilation systems:	- Ridge - Eaves - Top abutment - Tile vent - Gas terminals

See pages 64-77.

Colours

