

# Bold Roll



## Fittings and accessories

Tile fittings:	- Cloaked verge tiles (LH & RH) - Half tiles - Dentil slips
Ridges:	- Half round - Segmental
Mono ridges:	- Half round
Hips:	- Half round - Segmental
Eaves:	- Bird comb filler
Valleys:	- Lead - Fibreglass
Clips:	- Tile, Eaves, Verge

See pages 22-25.

## Roofing systems

Dry roof systems:	- Ridge, Hip - Verge
Ventilation systems:	- Ridge - Eaves - Top abutment - Tile vent - Gas terminals

See pages 64-77.

**A deep rolled profile that creates a strongly undulating roof surface with a Mediterranean feel.**

## Technical data

Minimum roof pitch	22.5°
Headlap (minimum)	75 mm
Headlap (maximum)	120 mm
Batten spacing at max. gauge	345 mm
Batten spacing at min. gauge	300 mm
Size of tile	420 x 334 mm
Covering capacity at max. gauge	9.7 tiles per m <sup>2</sup>
Cover width	300 mm
Profile depth	68 mm
Hanging length	394 mm
Weight as laid	48.0 kg per m <sup>2</sup>
Weight per 1000	4.9 tonnes
Weight per tile	4.9 kg
Weight per pallet (including pallet/packaging)	1.0 tonnes
Quantity per pallet	210
Battens per m <sup>2</sup>	2.91 m
Batten size	
Up to 450 mm rafter centres	38 x 25 mm
Up to 600 mm rafter centres	50 x 25 mm
Nail size/type for tiles	80 x 3.75 mm aluminium clout head
Nail size/type for tile clips	50 x 3.35 mm aluminium clout head

Note: Unless otherwise stated, data is based on tiles laid at minimum headlap.

## Colours

