

# Plain Tile



Plain Tile Rustic

## Fittings and accessories

Tile fittings: - Tile-and-a-half tiles  
- Eaves/tops tiles  
- Cloaked verge tiles (LH & RH)  
- External & internal angles (LH & RH)

Feature tiles - Club

Ridges: - Half round  
- Segmental

Mono ridges: - Half round

Hips: - Bonnet  
- Arris  
- Half round  
- Segmental

Valleys: - Valley tiles  
- Lead  
- Fibreglass

See pages 22-25.

## Roofing systems

Dry roof systems: - Ridge, Hip

Ventilation systems: - Ridge  
- Eaves  
- Top abutment  
- Tile vent  
- Gas terminals











See pages 64-77.

**This versatile cross-cambered concrete tile is perfect for complex detailing and curved roof applications.**

Technical data	Roof	Vertical
Minimum roof pitch	35°	75°
Headlap (minimum)	65 mm	38 mm
Batten spacing at max. gauge	100 mm	114 mm
Size of tile	265 x 165 mm	265 x 165 mm
Covering capacity at max. gauge	60.0 tiles per m <sup>2</sup>	53.0 tiles per m <sup>2</sup>
Cover width	165 mm	165 mm
Profile depth	13 mm	13 mm
Hanging length	245 mm	245 mm
Weight as laid	78.0 kg per m <sup>2</sup>	64.0 kg per m <sup>2</sup>
Weight per 1000	1.3 tonnes	1.3 tonnes
Weight per tile	1.3 kg	1.3 kg
Weight per pallet (including pallet/packaging)	1.0 tonnes	1.0 tonnes
Quantity per pallet	768	768
Battens per m <sup>2</sup>	10 m	8.7 m
Batten size		
Up to 450 mm rafter centres	38 x 25 mm	38 x 25 mm
Up to 600 mm rafter centres	38 x 25 mm	38 x 25 mm
Nail size/type for tiles	38 x 3.35 mm aluminium clout head	
Nail size/type for tile clips	N/A	N/A

Note: Unless otherwise stated, data is based on tiles laid at minimum headlap.

## Colours



## Feature tile

Club pattern available.

