

Lindum



Lindum Dark Grey and Terracotta Red

An interlocking concrete tile which provides a classic low profile roof.

Technical data

Minimum roof pitch	22.5° Smoothfaced 30° Sandfaced
Headlap (minimum)	75 mm
Headlap (maximum)	120 mm
Batten spacing at max. gauge	345 mm
Batten spacing at min. gauge	300 mm
Size of tile	420 x 334 mm
Covering capacity at max. gauge	9.7 tiles per m ²
Cover width	300 mm
Profile depth	42 mm
Hanging length	401 mm
Weight as laid	46.1 kg per m ²
Weight per 1000	4.8 tonnes
Weight per tile	4.8 kg
Weight per pallet (including pallet/packaging)	1.0 tonnes
Quantity per pallet	216
Battens per m ²	2.91 m
Batten size	
Up to 450 mm rafter centres	38 x 25 mm
Up to 600 mm rafter centres	50 x 25 mm
Nail size/type for tiles	50 x 3.35 mm aluminium clout head
Nail size/type for tile clips	50 x 3.35 mm aluminium clout head

Note: Unless otherwise stated, data is based on tiles laid at minimum headlap.

Fittings and accessories

Ridges: - Half round
- Segmental

Mono ridges: - Half round

Hips: - Half round
- Segmental

Valleys: - Lead
- Fibreglass

Clips: - Tile, Eaves, Verge

See pages 22-25.

Roofing systems

Dry roof systems: - Ridge, Hip
- Verge

Ventilation systems: - Ridge
- Eaves
- Top abutment
- Tile vent
- Gas terminals

See pages 64-77.

Colours

