

Standard Pattern



Standard Pattern Dark Grey

Fittings and accessories

Ridges: - Half round
- Segmental

Mono ridges: - Half round

Hips: - Half round
- Segmental

Valleys: - Lead
- Fibreglass

Clips: - Tile, Eaves, Verge

See pages 22-25.

Roofing systems

Dry roof systems: - Ridge, Hip

Ventilation systems: - Ridge
- Eaves
- Top abutment
- Tile vent
- Gas terminals

See pages 64-77.

Easy to install and highly durable, this tile is ideal for re-roofing and comes in convenient banded packs of eight.

Technical data

Minimum roof pitch	22.5° Smoothfaced 30° Sandfaced
Headlap (minimum)	75 mm
Headlap (maximum)	120 mm
Batten spacing at max. gauge	305 mm
Batten spacing at min. gauge	260 mm
Size of tile	380 x 230 mm
Covering capacity at max. gauge	16.5 tiles per m ²
Cover width	200 mm
Profile depth	40 mm
Hanging length	355 mm
Weight as laid	48.7 kg per m ²
Weight per 1000	3.0 tonnes
Weight per tile	3.0 kg
Weight per pallet (including pallet/packaging)	1.1 tonnes
Quantity per pallet	360
Battens per m ²	3.30 m
Batten size	
Up to 450 mm rafter centres	38 x 25 mm
Up to 600 mm rafter centres	50 x 25 mm
Nail size/type for tiles	50 x 3.35 mm aluminium clout head
Nail size/type for tile clips	50 x 3.35 mm aluminium clout head

Note: Unless otherwise stated, data is based on tiles laid at minimum headlap.

Colours

