

Product features & benefits

- In-line design
- Choice of three colours
- Fully wind tunnel tested
- Built in downpipe allows direct ventilation to roof space
- No soil/mechanical adaptor required

Area of application

Suitable for:

- 600 x 300mm (24" x 12") and 500mm x 250mm (20" x 10") fibre and natural double lap slates
- High or low level roof space ventilation
- Roof pitches over 22.5°
- Most natural and fibre cement slates

Material

UV resistant Polypropylene

Colours

Dark slate
Slate blue
Slate grey

Dimensions

600mm long x 300mm wide x 141mm deep

Weight (per carton)

11.5kg

Packaging

10 vents per carton
9 cartons per pallet

Product code

Dark slate KG963007
Slate blue KG963060
Slate grey KG963030

Flexipipe KG979900

Regulations and certifications

Complies fully with relevant Building Regulations and British Standards

Related products

When used as high-level ventilation, use in conjunction with Klover Eaves Ventilation products.



A universal In-line Slate Vent that suits most man-made and natural slates.



Installation

The vent is positioned directly in-line with the tile below, and an inverted T opening is cut within the underlay to accommodate the downpipe. To ensure the integrity of the underlay a Klover Underlay Seal is strongly recommended. Once the downpipe has been located through the underlay opening, the vent tile base is located on and fixed to the tiling batten. The front skirt is then dressed onto the top of the tile below, which should be clean, dry and free from dust. The roof tiles either side of the vent are laid and prior to the tile above being laid the upper skirt needs to be pushed down. Tile battens would need to be cut if plain tiles are being used.

Performance

Provides 12,000mm² ventilation area (6,500 mm² effective ventilation area)

Vent spacing	5,000 mm ² /m	install at 1.2 m centres
	10,000 mm ² /m	install at 0.6 m centres
Airflow resistance	15 litres/sec	24 Pascals
	30 litres/sec	96 Pascals
	60 litres/sec	384 Pascals